

MINIB[®]

●●● more than just heat

SPECIAL HEATING AND COOLING



FOR ALL TYPES OF INTERIORS

▶ AEGEAN SFC - INTEGRATED COOLING / HEATING FAN COILS



- central ceiling units for commercial use, as hotels, restaurants, offices
- the fancoil has several air outlets for the connection to HVAC which distributes the modified air to the outlet
- horizontal and vertical versions are available

APPLICATIONS

Education
Healthcare
Leisure and sport
Office
Hospitality
Retail
Showroom
Industrial

Model	Cooling output [kW]	Heating output [kW]	Total power consumption [W]	Dimensions [mm]		
				height	width	length
Aegean SFC 180H	0,25 - 6,23	0,59 - 3,97	1x28 - 2x95	180	1050 - 2107	910
Aegean SFC 235H	0,77 - 8,51	0,34 - 8,85	65 - 325	235	800 - 2300	845
Aegean SFC 260H	0,69 - 10,27	0,80 - 7,86	65 - 325	260	800-2300	845



heating



cooling



with a fan

▶ SKYLINE® - CEILING BUILT-IN ELECTRIC CONVECTOR



- convector into ceiling raster 600x600mm
- ideal for commercial buildings
- efficient heating of large spaces
- unobtrusive and effective
- the possibility of different color variants

APPLICATIONS

Education
Healthcare
Leisure and sport
Office
Hospitality
Retail
Industrial

Model	Heating output [kW]	Total power consumption [kW]	Dimensions [mm]		
			height	width	length
Skyline E 4kW	4	4,1	151	600	600



heating



with a fan

▶ CASPIAN SL - POWERFUL FAN CONVECTORS



- practical and high-quality heating solutions for commercial buildings
- standardly supplied with the latest technology of EC motor, cost saving up to 80% (models with AC motor on request)
- efficient and quiet operation
- possibility of anti-microbial or anti-bacterial coating
- the possibility of different color variants

APPLICATIONS

Education
Healthcare
Leisure and sport
Office
Hospitality
Retail
Showroom
Industrial

Model	Heating output [kW]	Total power consumption [W]	Dimensions [mm]		
			height	width	length
Caspian 60	0,8 - 5,9	8 - 40	660	235	595
Caspian 90	1,5 - 10,3	15 - 70	660	235	895
Caspian 120	1,3 - 14,5	13 - 110	660	235	1195
Caspian 150	4,8 - 16,2	20 - 177	660	235	1495
Caspian 180	6,6 - 19,2	26 - 220	660	235	1795



heating



with a fan

CASPIAN LST - LOW SURFACE TEMPERATURE CONVECTORS



- specially developed for hospitals and healthcare with strict hygiene regulations and low surface temperature
- possibility of anti-microbial or anti-bacterial coating
- universal convectors for commercial areas
- wall, under-ceiling or on-ceiling installation
- the possibility of different color variants

APPLICATIONS

Education
Healthcare
Office
Hospitality

Model	Heating output [kW]	Total power consumption [W]	Dimensions [mm]		
			height	width	length
Caspian 60	0,6 - 2,2	26 - 55	660	245	595
Caspian 90	1,6 - 3,9	33 - 85	660	245	895
Caspian 120	2,8 - 5,7	33 - 125	660	245	1195
Caspian 150	4,2 - 7,2	50 - 188	660	245	1495
Caspian 180	5,7 - 8,7	66 - 250	660	245	1795



heating



with a fan

SPACE SAVER - PLINTH CONVECTOR



- a highly energy efficient fan convector that fits neatly into the plinth of a kitchen unit and eliminates the need for conventional radiators
- ideal for kitchen skirtings or bathrooms
- for home use
- the possibility of different color variants

APPLICATIONS

Education
Healthcare
Office
Hospitality

Model	Heating output [W]	Dimensions [mm]		
		height	width	length
SS80	213 - 645	74	255	550
SS3	307 - 806	100	288	498
SS5	378 - 967	100	288	498
SS5-12V 1)	378 - 967	100	288	498
SS5-low 2)	378 - 967	100	288	498
SS7	426 - 1128	100	288	498



heating



with a fan

1) specially developed for bathrooms

2) suitable in combination with a heat pump

SURELINE® - PERIMETER CONVECTOR



- simple to install along the skirting in any room
- efficient natural convector that provides discreet heating
- ideal heating solution for areas where wall space is limited
- the possibility of different color variants

APPLICATIONS

Education
Healthcare
Leisure and sport
Office
Hospitality
Retail
Showroom
Industrial

HEATING OUTPUT [W]

length L [mm]	Top return - Bottom supply				Two supplies - Parallel			
	input / output water temperature [°C]	air temperature [°C]			input / output water temperature [°C]	air temperature [°C]		
		15	20	22		15	20	22
500	75/65	185	161	152	75/65	221	193	182
1000	75/65	413	360	340	75/65	494	431	407
1500	75/65	641	559	528	75/65	767	669	631
2000	75/65	869	759	716	75/65	1039	907	856



heating

MINIB[®]



●●● more than just heat



HEAD OFFICE

MINIB, a.s.

Střešovická 465/49, 162 00 Prague 6
Czech Republic

Tel.: +420 220 180 809

E-mail: export@minib.cz

www.minib.com

PRODUCTION

Manufacturing plant of MINIB, a.s.
Býkev u Mělníka 84, 276 01 Býkev
Czech Republic

